



LINGJACK

林傑

9KG ABC CARTRIDGE OPERATED FIRE EXTINGUISHER

MODEL : C-9ACE

Specification :

- Capacity : 9 kg
- Extinguishing Medium : 40% ABC Dry Chemical Powder
- Propellant Type : 150 gram CO₂
- Discharge Time : 19.4 sec
- Discharge Range : 7 m
- Working Pressure : 14.6 bar
- Working Temperature : -20Deg C to +60 Deg C
- Hose Length : 530 mm
- Size : Dia. 181 x 575(H) mm
- Finishing : Red Color RAL 3000
- Gross Weight : Approximate 13.5 kg



Features :

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Effective Suppression of Class A,B Fires
- Effective Suppression of Class C Fires
(Only Applicable To LPCB Approval Model)
- Suitable to Use on Live Electrical Equipment Up to 1000V
(Only Applicable To LPCB Approval Model)

Standards : Manufactured In Accordance With EN 3-7

Approvals : LPCB (UK), BUREAU VERITAS (BV)

Origin : Made in Singapore


Ordering Matrix :

| Com No. | Fire Rating | For Class Of Fire | Standard | Approval |
|----------------|-------------|-------------------|------------------------|----------|
| 20801608 | 43A, 233B | A, B, C | BS EN 3-7:2004+A1:2007 | LPCB |
| 20801608000001 | 43A, 233B | A, B, C | BS EN 3-7:2004+A1:2007 | BV (MED) |



EN3-7:2004 + A1:2007

Cert No. 501a



2690

GOOD QUALITY GREAT SERVICES

www.lingjack.com

LEW-MDS-C9ACE Rev00 (Dec21)

Specification subjects to change without prior notice